


GRAVOTAC™

See our Braille Solution p.48



• DDA & ADA compliant tactile signage

- 1 mm (1/32") single-ply profile material
- Available with or without adhesive backing
- 1.6 mm (1/16") single-ply substrates for backplate material

Specifications

Surface	Matt
Composition	ABS
Full sheet	1220 mm x 610 mm (24" x 48")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (12" x 24")

Capabilities


Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
		60°C	Max. temp.

Surface colour	1-ply	
	1.0 mm 1/32" profile	1.6 mm 1/16" backplate
bright white	28372	29879
almond	28370	29882
yellow	28368	29883
red	28361	29885
burgundy	28373	29888
pine green	28366	29895
metallic blue	28360	29896
azure blue	28369	29897
navy blue	28363	29898
taupe	28362	29890
candlewick	28374	29899
silver grey	28364	29900
slate	28367	29901
chocolate brown	28375	29892
black	28371	29902

GRAVOTAC™

EXTERIOR

NEW



- Indoor and outdoor use
- Cut with laser or C.N.C. machines

Specifications

Surface	Matt
Composition	Impact modified acrylic
Full sheet	1220 mm x 610 mm (24" x 48")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (12" x 24")

Capabilities

Interior	■	■	Exterior
Shear		■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■	■	UV resistant
		90°C	Max. temp.

Surface colour	1-ply	
	0.8 mm 1/32" profile	1.6 mm 1/16"
clear	29918	
exterior white	29919	29936
teal		29903
maui blue		45961
azure blue		29945
silver	29931	
gold	29932	
black	29920	29937