


# GRAVOFOIL

- Industrial signage
- Permanent labels

- Matt finish
- Very flexible
- Interior and exterior
- Excellent resistance to acids and solvents
- An assortment of 13 colours
- Comes with adhesive backing
- Colours for the identification of pipes in the industrial sector




ROTARY



INDOOR



OUTDOOR



SURFACE

|   | Surface colour | Core colour | 0.2 mm<br>.008" |
|---|----------------|-------------|-----------------|
| ● | white          | black       | 18448           |
| ● | black          | white       | 18446           |
| ● | blue           | white       | 18452           |
| ● | purple         | white       | 18469           |
| ● | yellow         | black       | 18456           |
| ● | brown          | white       | 18458           |
| ● | red            | white       | 18450           |
| ● | green          | white       | 18460           |
| ● | grey           | white       | 18454           |
| ● | orange         | black       | 18462           |
| ● | gold           | black       | 18464           |
| ● | silver         | black       | 21811           |
| ● | copper         | black       | 18467           |

## Specifications

|                 |                               |
|-----------------|-------------------------------|
| Surface         | Matt                          |
| Composition     | PVC                           |
| Engraving depth | 0.02 mm (.001")               |
| Full sheet      | 660 mm x 480 mm (25" x 18")   |
| Half sheet      | 480 mm x 330 mm (25" x 12.5") |

## Capabilities

|                   |       |      |              |
|-------------------|-------|------|--------------|
| Interior          | ■     | ■    | Exterior     |
| Shear             | ■     |      | Saw          |
| Silk screen       | ■     | ■    | Hot stamp    |
| Scratch resistant |       | ■    | Flexible     |
| Break resistant   | ■     | ■    | UV resistant |
| Min. temp.        | -40°C | 70°C | Max. temp.   |

Warning:

For laser engraving, use Stickalase. See p.17.

