

- Badges
- Identification plates
- Interior signage

- Microthin surface layer
- Perfect for small characters and detailed logos
- Low glare, matt finish

Specifications

Surface	Matt
Composition	ABS
Profile engraving depth	0.1 mm (.004")
Full sheet	1220 mm x 610 mm (24" x 48")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (12" x 24")

Capabilities

Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
		60°C	Max. temp.

Did you know?




We can custom manufacture your badges so that all you have to do is engrave. See page 10. Double-sided available on request in any of the standard colours.



			2-ply			
			0.5 mm	0.8 mm	1.5 mm	2.4 mm
	Surface colour	Core colour	.020"	1/32"	1/16"	3/32"
●	white	red		21857	21928	21989
●	white	burgundy			21874	
●	white	azure blue		21841	21908	21973
●	white	black	53218	21850	21919	21982
●	almond	burgundy			29709	
●	almond	black		21855	21926	
●	yellow	red			21913	
●	yellow	blue		21828	21896	
●	yellow	black		21863	21936	21995
●	dark yellow	black			21925	
●	orange	white			52205	
●	red	white	53219	21851	21921	21983
●	red	yellow			21910	
●	burgundy	white			21932	
●	apple green	white		21838	21905	21970
●	pine green	white		21865	21938	21997
●	pine green	yellow			21916	
●	sky blue	white		21861	21934	21993
●	sky blue	black			21895	
●	blue	white	53220	21852	21923	21984
●	blue	yellow			21911	
●	air force blue	white			21907	
●	brown	white		21858	21930	
●	chocolate brown	white			21876	
●	grey	white		21856	21927	21988
●	grey	black			21915	
●	black	white	53217	21849	21917	21981
●	black	yellow		21866	21940	

* Gravoply™ 2 products have a laserable foil cap, but their ABS core does not react well to lasering. When engraving with a laser, please ensure that you do not engrave deep into the ABS core.

GRAVOPLY™ 2



- **Badges**
- **Identification plates**
- **Interior signage**

The ultimate in scratch resistance!

Gravoply™ 2



- Gravoply™ 2 Gloss has an extra durable, scratch resistant, glossy cap
- Microthin surface layer
- Perfect for small characters and detailed logos
- Low glare, matt finish on Tech Patterns

			2-ply
			1.5 mm
	Surface colour	Core colour	1/16"
●	white	red	23981
●	white	black	23977
●	yellow	black	23982
●	red	white	23978
●	emerald green	white	23983
●	blue	white	23979
●	grey	white	23980
●	black	white	23976

Specifications

Surface	Matt, Glossy
Composition	ABS
Profile engraving depth	0.1 mm (.004")
Full sheet	1220 mm x 610 mm (24" x 48")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (12" x 24")

Gravoply™ 2 wood

			2-ply
			1.5 mm
	Surface colour	Core colour	1/16"
●	satin light walnut	white	21885

Capabilities

Interior	■		Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant	■		UV resistant
		60°C	Max. temp.

Gravoply™ 2 Tech Patterns

			2-ply
			1.5 mm
	Surface colour	Core colour	1/16"
●	black pinstripe	white	22019
●	silver grid	black	22022

* Gravoply™ 2 products have a laserable foil cap, but their ABS core does not react well to lasering. When engraving with a laser, please ensure that you do not engrave deep into the ABS core.