


GRAVOPLY™ ULTRA

- Badges
- Awards plaques
- Indoor and outdoor signage



- Satin or matt finish
- Unique 0.5 mm (.002") cap layer for detailed engraving
- UV stable
- Excellent for photo lasering
- Reduce inventory with one material for rotary, laser, indoor and outdoor needs

Specifications

Surface	Satin or Matt
Composition	DR Acrylic
Rotary engraving depth	0.1 mm (.004")
Full sheet	1220 mm x 610 mm (24" x 48")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (12" x 24")

Capabilities

Interior	■	■	Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■	■	Flexible
Break resistant		■	UV resistant
		80°C	Max. temp.

			Matt 2-ply		Satin 2-ply	
			0.5 mm	1.6 mm	1.6 mm	2.4 mm
	Surface colour	Core colour	.020"	1/16"	1/16"	3/32"
○	clear*	white	18965	19009		
●	clear*	black	18962	19006		
●	white	red		18997		
●	white	blue		18996		
●	white	black	18946	18984	29507	
●	yellow	black	18955	18993	29511	
●	orange	white		19000		
●	orange	black		29499		
●	red	white	18949	18987	29512	
●	red	black		29498		
●	red	gold		29503		
●	burgundy	white		18980		
●	burgundy	gold	18958	18999		
●	green apple	white	18970	19012	29513	
●	forest green	white		19001		
●	forest green	gold		18998		
●	pine green	white		29491		
●	blue	white	18952	18990	29510	
●	navy blue	white		29494		
●	royal blue	white		19015		
●	royal blue	gold	18942	18979		
●	brown	white		29495		
●	black	white	18943	18981	29508	29687
●	black	silver grey		19005		
●	glossy black	gold	18973			
●	matt black	gold	18976	19004		

* Suitable for subsurface engraving.

Gravoply™ Ultraglow



NEW

Photoluminescent

			Matt 2-ply
	Surface colour	Core colour	0.8 mm (1/32")
○	glow	white	49884

Please note:

This product allows for white engraving on the photoluminescent surface. 0.8 mm (1/32") thickness may be used to cut profile letters for DDA tactile signage applications. The glow times for this product meet the following norms: ISO:10012-1 & MIL-STD-45662A