




GRAVOSTRAT®



• Industrial identification

- Phenolic material
- Glossy finish
(matt finish for photoluminescent)
- Double-sided
- Resistant to chemicals and solvents
- Non-flammable
- Conforms to military specifications
ASTM D 709 ES-1, ES-2, ES-3
- Electrically non-conductive
- Scratch resistant
- Saw cut
- Indoor use

			double-sided		
			1.0 mm*	1.5 mm*	2.4 mm**
	Surface colour	Core colour	.040"	1/16"	3/32"
●	white	red		22045	22052
●	white	blue		18496	18516
●	white	black	30385	22042	22049
●	ivory	black		18500	18520
●	yellow	black	30389	22044	22051
●	orange	white		18492	18512
●	red	white	30390	22043	22050
●	green	white	30392	22046	22053
●	blue	white	30393	18489	18509
●	grey	black		22047	22054
●	black	yellow		18498	18518
●	black	white	30395	22041	22048

** Gravostrat may be subject to slight variations in thickness

			1.2 mm
	Surface colour	Core colour	.050"
●	photoluminescent	brown	18525

Size: 605 x 605 mm

Specifications

Surface	Glossy, matt for photoluminescent
Composition	Rigid thermoset material
Profile engraving depth	0.3 mm (.012")
Full sheet	1220 mm x 605 mm (24" x 48")
Half sheet	610 mm x 605 mm (24" x 24")
Quarter sheet	605 mm x 305 mm (12" x 24")

Capabilities

Interior	■		Exterior
Shear		■	Saw
Silk screen	■		Hot stamp
Scratch resistant	■		Flexible
Break resistant			UV resistant
		60°C	Max. temp.

* Gravostrat® can be laser engraved but not laser cut.