





GRAVOXAL



- Control panels
- Legend plates
- Award plaques
- Signage

- Anodised aluminium
- For rotary or laser engraving

Specifications

Surface	Matt or Glossy
Composition	Aluminium
Profile engraving depth	0.1 mm (.004")
Full sheet	1000 mm x 500 mm (39" x 19")
Other size	2000 mm x 1000 mm (78" x 39")

Capabilities

Interior	■	■	Exterior
Shear	■	■	Saw
Silk screen	■	■	Hot stamp
Scratch resistant	■		Flexible
Break resistant	■	■	UV resistant
Min. temp.	-40°C	100°C	Max. temp.

Matt

		0.5 mm	1.0 mm	1.5 mm	2.0 mm	2.5 mm	3.0 mm	4.0 mm
	Surface colour	.02"	.04"	1/16"	1/12"	3/32"	1/8"	1/6"
○	champagne		18581	18595	18608			
●	red		18577	18591	18605			
●	green		18583	18597	18610			
●	blue		18579	18593	22058			
●	silver	18385	22055	18386	22057	18387	22059	18388
●	gold	18571	18575	18589	18603		18616	
●	bronze		18585	18599	18612			
●	black	18569	18573	18587	18601		18614	

Glossy

		1.0 mm	1.5 mm	2.0 mm
	Surface colour	.40"	1/16"	1/12"
○	champagne	18640	18662	18681
●	red	18636	18658	18677
●	green	18642	18664	18683
●	blue	18638	18660	18679
●	silver	18618	18646	18668
●	steel-look	30381	30382	30383
●	gold	18630	18654	18674
●	bronze	18644	18666	18685
●	black	18624	18650	18671

Silver colours are anodised on both sides during the continuous anodisation process. Protective film on one surface.* Laser engraving on coloured material. Quality of engraving may vary according to the colour. Use Gravolaque to colour any GravoXal engraving. Aloxide may be used to colour Glossy finish. See p.36.